

# testo 350S/XL protective Pelican case

**NEW!**

The new impact-proof Pelican protection case is suitable for all areas where the testo 350 must be protected from impacts and thus is essential for heavy duty applications

The Pelican case has been optimised with smart design changes by Testo, effectively protecting the testo 350S/XL in all applications

## Technical features

### Easy transport

The case is equipped as follows:

- Extendable handle (trolley like functions)
- Stainless steel ball-bearing wheels in the base plate

### Higher security against theft and scratches

- Stainless steel reinforcement at the catches for the secure attachment of a padlock
- Strong and flexible against external impacts.
- The cases are manufactured with a special "sandwich" design. This allows for a layer of "foam plastic" to be present between two solid layers of copolymer polypropylene creating a total wall thickness of 63mm and therefore minimising more weight than a conventional injection moulding procedure, without compromising stability. This also makes it possible to use the Pelican case with the testo 350 inside as regular baggage on a flight

### Fast setup for use of the testo 350S/XL

Through a cover in the base plate of the case, all the connections of the testo 350S/XL are accessible externally (e.g. databus, power cable, gas sampling probe etc.). The Pelican case only requires the cover to be opened in order to connect all necessary lines and wires.

### Applications in rough conditions – protection class IP42

For the ideal ventilation of the testo 350S/XL, the Pelican case comes equipped with a ventilator. A thermal switch automatically switches on during at outside temperature of  $>15^{\circ}\text{C}$  and off at outside temperatures of  $<15^{\circ}\text{C}$ .

This allows for the use of the testo 350S/XL in the closed case with ambient temperatures from  $-10^{\circ}\text{C}$  to  $+50^{\circ}\text{C}$  (when there is no direct exposure from the sun)

- An integrated filter provides additional protection to the testo 350S/XL from dust and particles in ambient air.
- The case maintains the requirements of the IP 42 protection class even when the cover is open.

**PRICE: \$1132 + GST**

### Testo Pty Ltd

Tel: (03) 9800 4677 • Fax (03) 9800 4699

PO Box 2041, Bayswater, Victoria, 3153

Email: [info@testo.com.au](mailto:info@testo.com.au) • Website: [www.testo.com.au/testo350](http://www.testo.com.au/testo350)

